## PRIVATE SWIMMING POOLS AND SPAS REQUIRED INFORMATION FOR INSPECTIONS AND POOL APPLICATIONS FLORIDA BUILDING CODE **6TH EDITION (2017) RESIDENTIAL, CHAPTER 45**

City of Port Richey requires the following information to process applications for private swimming pools. Applicants are required to provide a pool layout showing:

- 1. The pool with a complete plumbing plan showing the location of the mechanical equipment and the plumbing lines, vent lines, pipe sizes, flow rates, and pressures.
- 2. The layout of the pool with dimensions showing steps, swimouts, ladders, and other features.
- 3. The spa with a plumbing plan.
- 4. The deck with dimension showing relationship to the house.
- 5. Location of windows and doors that have access to the pool from the house.
- 6. The location of the child barrier fence.

Applic	ants are required to provide	the following information:		
1.	Pool volume:	gallons		
2.	Pump Mfg.:	Model No.:	Turnover Rate:	GPM
	HP.:	<del></del>		
3.	Filter Mfg.:	Model No.:	Flow Rate:	GPM
4.	Pool Heater Mfg.:	Model No.:		
5.	Anti-Vortex Covers Mfg.:	Model No.:		
Applio Florid	cants are required to provid a Building 6+h	le design drawings showing pool and spa Residential, certified by a Florida re	requirements designed to gistered engineer or arch	o meet the itect.

The applicant shall provide two copies of all the above information. This information shall be supplemental to the normal permitting materials necessary at intake.

## RESIDENTIAL SWIMMING POOL, SPA, AND/OR HOT TUB SAFETY ACT NOTICE OF REQUIREMENTS

. --. "

addres	acknowledge that a new swimming pool, spa, or hot tub will be constructed or installed at (please print street s) and hereby affilm that one of the green methods will be used to meet the requirements of Florida Statutes (F.S.) 515:
	initial the method(s) to be used for your pool.
	The pool will be isolated from access to the home by an enclosure that meets the pool barrier requirements of F.S. 515.29.
	The pool will be equipped with an approved, safety-pool cover that complies with ASTM F1346 (Standard Performance Specifications for Safety Covers for Swimming Pools, Spas, and Hot Tubs).
	All doors and windows providing direct access from the home to the pool and located within the enclosure/fence required by F.S.515, will be equipped with an exit alarm that has a minimum sound pressure rating of 85 decibels at ten feet.
	All doors providing direct access from the home to the pool and located within the enclosure/fence required by F.S. 515.27 (d), will be equipped with self-closing, self-latching devices with release mechanisms placed no lower than 54 inches above the floor or deck.
FINAL VIOLA	ERSTAND AND AGREE THAT NOT HAVING AT LEAST ONE OF THE ABOVE INSTALLED AT THE TIME OF INSPECTION OR WHEN THE POOL IS COMPLETED FOR CONTRACT PURPOSES WILL CONSTITUTE A TION OF F.S. 515, AND WILL BE CONSIDERED AS COMMITTING A MISDEMEANOR OF THE SECOND EE, PUNISHABLE BY FINES UP TO \$500.00 AND/OR UP TO 60 DAYS IN JAIL AS ESTABLISHED IN F.S. 775.
pool st locked, require	17.1.10: Where an aboveground pool structure is used as a barrier or where the barrier is mounted on top of the ructure and the means of access is a ladder or steps, the ladder or steps shall either be capable of being secure, or removed to prevent access, or the ladder or steps shall be surrounded by a barrier which meets the ments of R4501.17.1.1 through R4501.17.1.9 and R4501.17.1.2 through R4501.17.1.4. When the ladder or steps sured, locked, or removed, any opening created shall not allow the passage of a four-inch diameter sphere.
FOLLO	THER UNDERSTAND AND AGREE THAT THE <u>OWNER AND/OR CONTRACTOR</u> WILL COMPLY WITH THE WING REGULATIONS CONCERNING SWIMMING POOL, SPA, AND/OR HOT TUB ENCLOSURES DIATELY UPON COMPLETION OF THE SWIMMING POOL, SPA, OR HOT TUB, IN COMPLIANCE WITH F.S. ITER 515:
1.	Construct around the swimming pool, spa, or hot tub a MINIMUM FOUR-FOOT-HIGH FENCE with self-closing, self-latching gates. The fence must not have any gaps, openings, indentations, protrusions, or structural components that could allow a young child to crawl under, squeeze through, or climb over the fence. Gates must open outward, away from the pool area. The releasing mechanism of the latching device must be located on the pool side of the gate and so placed that it cannot be reached by a young child over the top or through any opening or gap. No opening in the fence may be large enough to admit a four-inch sphere.
2.	Construct a screen enclosure around the swimming pool, spa, or hot tub with self-closing, self-latching, screen doors. Latches on exterior, screen doors must be a minimum of 54 inches from the exterior access standing surface. All screen enclosures require Building Permits.
3.	Provide and utilize an approved, safety, swimming pool, spa, or hot tub cover that complies with ASTM F1346 (Standard Performance Specifications for Safety Covers for Swimming Pools, Spas, and Hot Tubs). Such cover must be capable of being securely fastened over the swimming pool, spa, or hot tub when not in use.
I FUR	THER UNDERSTAND AND AGREE THAT one of the enclosures described above will be completed prior to final tion of the pool, spa, or hot tub.
hie/her	IONALLY, I FURTHER UNDERSTAND AND AGREE THAT the owner will require his/her pool contractor and screen-enclosure contractor (if applicable) to request and successfully pass a final inspection immediately ng the completion/installation of the swimming pool, spa, or hot tub.
IF THE	ESIGNATURE of the contractor acting as agent for the owner appears below, the contractor promises in good faith e the owner aware of the above-described requirements and penalties before commencing construction.
SWOF	IN AND SUBSCRIBED BEFORE ME THIS
	DAY OFOWNER OR CONTRACTOR SIGNATURE
	NOTARY PUBLIC PLEASE TYPE OR PRINT NAME ABOVE